



Terminal Type	Brand	DIN Rail Compatibility	Connection Type	Typical Voltage Rating ** V	Cable CSA (mm <sup>2</sup> ) mm <sup>2</sup>	Typical stock no.
				**Dependent on Approvals		
SAK series*	Weidmüller	G	Screw clamp	300 to 750 V	2.5 – 35	425-594
W series*	Weidmüller	Top Hat	Screw clamp (2 conductors)	300 V to 800 V	1.5	220-4131
Miniature AKZ series	Weidmüller	Top Hat	Screwless (Tension clamp)	800 V	4.0	823-342
BL series connector compatible	Weidmüller	G and Top Hat	Screw clamp	300	1.5	232-572
Z series	Weidmüller	Top Hat	Screwless (Tension clamp)	400 V to 800 V	4.0 – 16	225-9894
Z Miniature series	Weidmüller	Mini Top Hat	Screwless	500 V	0.5 to 2.5	445-8964
I series	Weidmüller	Top Hat	IDC	500 V	1.5 – 2.5	459-3720
5000 Universal series *	Entrelec	G and Top Hat	Screw clamp	300 V to 1000 V	2.5 – 300	426-171
Entrelec screwless	Entrelec	Top Hat	Spring cage clamp	(Grey) 600 V /(Yellow) 300 V (UL)	2.5 – 10	445-9349
Entrelec ADDO IDC	Entrelec	Top Hat	IDC	630 V to 1000 V	0.34 - 1.5 and 1.0 - 2.5	218-9183
Miniature and Micro	Entrelec	Mini Top Hat	Screw clamp	200 (300) V to 500 V	up to 4	277-9174
UK*	Phoenix Contact	G and Top Hat	Screw	750 V(ac)	2.5 – 10	101-2751
MT Series*	Phoenix Contact	Mini Top Hat	Screw clamp	400 V	0.14 - 1.5	869-051
ST series	Phoenix Contact	Top Hat	Screwless	800 V	0.2 - 6.0	388-4592
OTTA series	Phoenix Contact	G and Top Hat	Bolt	800 V	0.1 - 6.0 and 1.0 - 2.5	290-2706
870 Series	Wago	Top Hat	Screwless	500 V	0.08 - 2.5 and 4.00	388-7434
264 Miniature	Wago	Mini Top Hat	Screwless	750 V(ac)	0.8 - 2.5	484-3889
Commercial	Weidmüller	G and Top Hat	Screwless	300 - 750	1.5 - 4	815-638

**Note:** \* Hazardous area compatibility